

## TRUSTSEAL LTD

Unit 10 Southfield Lane Ind. Est.  
Whitwell Worksop S80 4NW  
Tel 01909 722662 Fax 01909 720228  
Web Site <http://www.trustseal.co.uk>  
Email [info@trustseal.co.uk](mailto:info@trustseal.co.uk)



# PRODUCT SPECIFICATION COLOURED AGGREGATES

## Description

Trustseal can colour most aggregates to meet British and European Standard colour range. The aggregates most commonly used are Bauxite, Harden Red, Criggion Green and Quartz. These are coated using a Polyurethane binder to provide a high visibility, hard wearing skid resistant surface.

## High PSV Aggregates

The most commonly used high PSV aggregates are Guyanan or Chinese Bauxite, which give PSV's in the range of 70-75. Harden Red and Criggion Green have PSV's in the range of 65-70.

## Physical Properties of the Binder

	Typical	Minimum
Tensile Strength BS 2782	14N/mm <sup>2</sup>	10.5N/mm <sup>2</sup>
Elongation	45%	30% Min

## Coverage Rates

Aggregate	8-9 Kg/m <sup>2</sup>
Packaging	25 kg Bags

## Health and Safety

Coloured Aggregates presents no health hazard.

Other information refer to product Health and Safety Sheet.

The above information is only intended for guidance and customers are urged to ensure that the product is entirely suitable for their own purpose.



MANUFACTURERS OF  
KEYGRIP EPOXY TYPE ONE HIGH FRICTION SURFACING  
KEYGRIP THERMOPLASTIC TYPE ONE AND TYPE THREE HIGH FRICTION SURFACING  
COLOURED TRAFFIC CALMING PRODUCTS : JOINT AND OVERBAND SEALANTS  
INSTALLERS OF  
ANTI-SKID SURFACING : TRAFFIC CALMING CYCLE LANES ETC  
REFLECTIVE CRACKING TREATMENTS : ASPHALT AND CONCRETE REPAIR